




NanoFrazor[®] Scholar

ADVANCED NANOLITHOGRAPHY FOR EVERYONE




NanoFrazor® Scholar

TABLETOP DIRECT WRITE NANOLITHOGRAPHY


The NanoFrazor® Scholar is an entry-level nanopatterning system with many unique capabilities. It is particularly well-suited for academic research groups as a simple tool to easily create their own high-quality nanopatterns and devices.

NanoFrazor lithography systems are based on thermal scanning probe lithography. Core of the NanoFrazor® technology is an ultra-sharp heatable probe tip which is used for writing and simultaneous inspection of complex nanostructures. The heated tip creates arbitrary, high-resolution nanostructures by local sublimation of resists. Standard pattern transfer methods like lift-off or etching can be applied.

Patented "Closed-Loop Lithography" ensures high patterning accuracy



NANOFRAZOR CANTILEVERS




- Ultra-sharp Si tip
- Integrated tip heater
- Integrated force actuation
- Integrated topography sensor
- Fast exchange and calibration

RAPID PROTOTYPING OF NANODEVICES

- Thermal probe lithography is the fastest of all scanning probe lithography methods (few μs exposure per pixel).
- Direct resist removal and in-situ inspection enable fast turn-around times.
- Detection of features buried under resist (e.g. 2D material flakes, nanowires, ...) for quick and accurate overlay of electrodes.

ULTRA-HIGH RESOLUTION



Gap between two metal electrodes made with a simple lift-off process Trimers etched into gold


NANOPATTERNING OF SENSITIVE MATERIALS AND DEVICES

NANOFRAZOR LITHOGRAPHY

The tip heats the top resist layer only. Material below the resist (e.g. 2D materials, topological insulators, nanowires, etc) remain completely unharmed during patterning of the resist. The NanoFrazor® can be incorporated inside a glovebox. This facilitates nanolithography on samples that deteriorate in air.


CHARGED-PARTICLE LITHOGRAPHY

Exposure to high-energy charged particles damages samples by unwanted creation & scission of covalent bonds, vacancies, trapped charges or lattice defects. Such defects deteriorate the device performance when using sensitive materials or designs.



MoS₂ top-gate transistors with record on/off ratios of 10¹⁰. Significantly less damage and resist residues compared to contacts made by EBL lead to vanishing Schottky barriers at the contacts.

Courtesy of Riedo group at NYU, see Zheng et al, Nat. Electronics 2019




NanoFrazor Scholar inside a custom designed glovebox from MBraun

NANOSCALE MATERIAL CONVERSION

The heated tip can alternatively be used to induce highly localized modification of materials: Deprotection of functional groups, precursor conversion, amorphization, crystallization, change of magnetic orientation, etc.

OTHER UNIQUE CAPABILITIES

- **3D grayscale lithography** with unprecedented accuracy enabled by closed-loop lithography
- **Accurate overlay and stitching** without artificial markers, achieved by topography imaging



NanoFrazor® Scholar

SYSTEM SPECIFICATIONS

Patterning performance

Minimum structure size [nm]	20
Minimum lines and spaces [half pitch, nm]	30
Grayscale / 3D-resolution (step size in PPA) [nm]	3
Writing field size [X μm x Y μm]	50 x 50
Field stitching accuracy (markerless, using in-situ imaging) [nm]	50
Overlay accuracy (markerless, using in-situ imaging) [nm]	50
Write speed (typical scan speed) [mm/s]	0.5
Write speed (50 nm pixel) [$\mu\text{m}^2/\text{min}$]	500

Imaging performance

Lateral imaging resolution (feature size) [nm]	10
Vertical resolution (topography sensitivity) [nm]	<0.5
Imaging speed (@ 50 nm resolution) [$\mu\text{m}^2/\text{min}$]	500

System features

Substrate sizes	1 x 1 mm ² to 50 x 50 mm ² (100 x 100 mm ² possible with limitations) Thickness: 5 mm with optical access, 10 mm without optical access
Optical microscope	0.6 μm digital resolution, 2.4 μm diffraction limit, 1.0 mm x 1.0 mm field of view
Magnetic cantilever holder	Fast (<1 min) and accurate tip exchange
Housing	Compact housing with separate controller rack, active vibration isolation
Software features	GDS and bitmap import, topography image analysis and drawing for overlay, fully automated calibration routines, Python scripting

NanoFrazor cantilever features

Integrated components	Tip heater, topography sensor, electrostatic actuation
Tip geometry	Conical tip with < 10 nm radius and 750 nm length
Tip heater temperature range	25 °C – 1100 °C (< 1 K setpoint resolution)

System dimensions & installation requirements

Height x width x depth	Table top: 40 cm x 40 cm x 45 cm, electronic trolley: 66 cm x 56 cm, x 60 cm
Weight	100 kg
Power input	1 x 110 or 220 V AC, 10 A
Vibration and noise level	Ambient acoustic noise levels need to be kept below 40 dB for best performance. A strong table is required. Floor requires vibration level VC-B.

Other considerations

Recipe book with detailed descriptions of various processes is available (regularly updated with software).

Cantilever tips degrade over time (> 50 h patterning possible). Exchange is fast and low cost for tool owners.

A cleanroom or special laboratory is not required. No vacuum needed.

Unique capabilities make it easy to receive government funding (for system itself or later research projects).



Tel: +86-512-62529622

Fax: +86-512-62522966

苏州工业园区北摆宴街8号
恒润商务大厦一楼A-3



www.stella-litho.com

联系人: 江俊葳 先生 / Wesley
移动电话: +86 186 0621 7371
Email: wesley@stella-litho.com



联系人: 邱重铠 先生 / CK
移动电话: +86 180 3682 6293
Email: ckchiu@stella-litho.com

